

Double Raschel

Features

- ① Ultra - lightweight
- ② High elasticity
- ③ Excellent durability (intensity retention)
- ④ Superb aeration properties

Application

- ① Automobile sheets (non-urethane)
- ② Bedding mats
- ③ Partitions for business offices
- ④ Backing material for concrete
- ⑤ Archery mats

Test data

【Warp knit specification】

Item		Product name
		Spacer
Knitting structure		Double Raschel
Machine width		130inch
Gauge		9G
Thread specification	Thread type	Spun - dyed polyester
	Warp	470T
	Warp core	330T
	Insertion from side	470T
Resin treatment		None
Dimension of mesh	Vertical	6mm
	Horizontal	6mm
Thickness	Vertical	5mm
	Horizontal	
Tensile strength	Vertical	2.54 (KN)
	Horizontal	1.18 (KN)
Elasticity	Vertical	64.1%
	Horizontal	80.3%

FUKUI FIBERTECH CO., LTD

5-1 IWANISHI, NAKAHARA-CHO, TOYOHASHI, AICHI, JAPAN TEL 81-50-7529-2085 / 81-532-41-1211 FAX 81-532-41-5078
Contact person : Mark Inaoka E-mail : fukui-fibertech@global-c.biz <http://www.fukui-fibertech.co.jp>